## NSN 5925-01-330-5272



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-01-330-5272 **Body Style:** Rectangular dimensional envelope **Overall Length:** 16.719 inches **Overall Height:** 5.062 inches **Overall Width: 7.500** inches **Case Material: Plastic Fragility Factor:** Moderately rugged **Pole Quantity: Arc Quenching Method:** Magnetic blowout **Mounting Facility Type And Quantity:** 4 unthreaded hole Storage Type: General purpose warehouse **Maximum Continuous Load Current Rating Per Pole:** 15.0 amperes ac all locations and 15.0 amperes dc all locations **Operating Voltage Type And Rating Per Pole In Volts:** 600.0 ac all locations and 250.0 dc all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 18000.0 ac all locations and 30000.0 dc all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Thermal all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 all locations **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 1 toggle **Actuator Function:** Trip-reset

At pole one

**Actuator Position Designation:** 

## NSN 5925-01-330-5272

Circuit Breaker - Page 2 of 2



Internal Trip Release Configuration:
Series trip all locations
Inclosure Protection Type For Which Designed:
Dustproof and fungus proof
Trip Release Ambient Tempurature Rating:
50.0 degrees celsius all locations
Frequency In Hertz:
60.0 all locations
Terminal Type And Quantity:
4 compression
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A030a0