

View Online at <https://aerobasegroup.com/nsn/5925-01-330-5274>

**Body Style:**

Single pole type

**Body Length:**

Between 1.550 inches and 1.570 inches

**Body Width:**

Between 0.760 inches and 0.780 inches

**Body Height:**

Between 1.810 inches and 1.870 inches

**Case Material:**

Plastic

**Switch Contact Arrangement:**

Single pole, double throw

**Fragility Factor:**

Moderately rugged

**Boss Height:**

Between 0.920 inches and 0.940 inches

**Pole Quantity:**

1

**Arc Quenching Method:**

Magnetic blowout

**Mounting Facility Type And Quantity:**

2 clip

**Storage Type:**

General purpose warehouse

**Maximum Continuous Load Current Rating Per Pole:**

15.0 amperes dc single location

**Operating Voltage Type And Rating Per Pole In Volts:**

32.0 dc single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

1000.0 dc single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Magnetic single location

**Trip Release Characteristic:**

Time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 single location

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole one

**Auxiliary Switch Function And Quantity:**

1 alarm

**Internal Trip Release Configuration:**

Series trip single location

**Switch Location And Position Designation:**

External at pole one

**Trip Delay Time In Seconds Per Rated Continuous Current:**

1.000 at 200 pct single location and 15.000 at 200 pct single location

**Inclosure Protection Type For Which Designed:**

Dustproof and fungus proof

**Switch Terminal Type:**

Tab, solder lug

**Switch Current Rating And Type In Amps:**

7.5 ac and 7.5 dc

**Switch Voltage Rating And Type In Volts:**

250.0 ac and 50.0 dc

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0