## NSN 5925-01-330-7613



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-01-330-7613 **Body Length:** 17.500 inches **Body Width:** 8.500 inches **Body Height:** 5.062 inches **Case Material: Plastic Fragility Factor:** Moderately rugged **Pole Quantity:** 3 **Arc Quenching Method:** Magnetic blowout **Mounting Facility Type And Quantity:** 4 unthreaded hole Storage Type: General purpose warehouse **Maximum Continuous Load Current Rating Per Pole:** 100.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 600.0 ac all locations **Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:** 18000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Thermal-magnetic all locations **Trip Release Characteristic:** Instantaneous all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 all locations **Reset Method:** 

Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 1 toggle **Actuator Function:** Trip-reset **Actuator Position Designation:** At pole two

## NSN 5925-01-330-7613

Circuit Breaker - Page 2 of 2



Inclosure Protection Type For Which Designed:
Dustproof and fungus proof
Trip Release Ambient Tempurature Rating:
40.0 degrees celsius all locations
Frequency In Hertz:
60.0 all locations
Terminal Type And Quantity:
6 compression
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A030a0