## NSN 5925-01-330-9203



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-01-330-9203 **Body Length:** 17.500 inches **Body Width:** 8.500 inches **Body Height:** 5.062 inches **Case Material: Plastic Fragility Factor:** Moderately rugged **Pole Quantity:** 3 **Arc Quenching Method:** Magnetic blowout **Mounting Facility Type And Quantity:** 4 unthreaded hole Storage Type: General purpose warehouse **Maximum Continuous Load Current Rating Per Pole:** 50.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 600.0 ac all locations **Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:** 18000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Thermal-magnetic all locations **Trip Release Characteristic:** Instantaneous all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 all locations **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 1 toggle **Actuator Function:** 

Trip-reset

**Actuator Position Designation:** 

At pole two

## NSN 5925-01-330-9203

Circuit Breaker - Page 2 of 2



| Internal Trip Release Configuration:          |
|---|
| Series trip all locations                     |
| Inclosure Protection Type For Which Designed: |
| Dustproof and fungus proof                    |
| Frequency In Hertz:                           |
| 60.0 all locations                            |
| Terminal Type And Quantity:                   |
| 6 compression                                 |
| Shelf Life:                                   |
| N/a   |
| Unit Of Measure:                              |
|   |
| Demilitarization:                             |
| No  |

Fiig: A030a0