NSN 5925-01-331-0235

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-331-0235

## **Body Style:**

Rectangular dimensional envelope

#### **Overall Length:**

2.170 inches

## **Overall Height:**

1.610 inches

## **Overall Width:**

1.770 inches

#### **Case Material:**

Plastic

Pole Quantity:

## 3

## Mounting Facility Type And Quantity:

2 clip

## Maximum Continuous Load Current Rating Per Pole:

1.5 amperes ac all locations

## **Operating Voltage Type And Rating Per Pole In Volts:**

250.0 ac all locations

## Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac all locations

## Circuit Protection Type:

Overcurrent all locations

## Trip Release Method:

Magnetic all locations

## **Trip Release Characteristic:**

Time delay all locations

#### Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

150.0 all locations

## **Reset Method:**

Manual

#### Main Contact Tripping Mechanism Type:

Trip free

# Manual Actuator Type And Quantity:

1 toggle

# Actuator Function:

Trip-reset

# Actuator Position Designation:

At pole two

# Internal Trip Release Configuration:

Series trip all locations

# Trip Delay Time In Seconds Per Rated Continuous Current:

0.050 at 200 pct all locations

# NSN 5925-01-331-0235

Circuit Breaker - Page 2 of 2

Frequency In Hertz:

400.0 all locations

# Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A030a0

