# NSN 5925-01-331-6994

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-331-6994

## Body Style:

Rectangular dimensional envelope

## **Overall Length:**

22.562 inches

# **Overall Height:**

3.875 inches

## **Overall Width:**

8.250 inches

#### **Case Material:**

Plastic

## **Unthreaded Mounting Hole Diameter:**

0.196 inches

## Fragility Factor:

Moderately rugged

## **Pole Quantity:**

3

#### Arc Quenching Method:

Magnetic blowout

## Mounting Facility Type And Quantity:

4 unthreaded hole

## Storage Type:

General purpose warehouse

## **Special Handling Feature:**

Magnetic

## **Features Provided:**

Adjustable trip release

## Maximum Continuous Load Current Rating Per Pole:

350.0 amperes ac all locations

## **Operating Voltage Type And Rating Per Pole In Volts:**

480.0 ac all locations

## Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

100000.0 ac all locations

## **Circuit Protection Type:**

Overcurrent all locations

## Trip Release Method:

Thermal-magnetic all locations

## **Trip Release Characteristic:**

Instantaneous all locations

## Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

## **Reset Method:**

Manual

# NSN 5925-01-331-6994

Circuit Breaker - Page 2 of 2



Main Contact Tripping Mechanism Type: Trip free Manual Actuator Type And Quantity: 1 toggle **Actuator Function:** Trip-reset **Actuator Position Designation:** At pole two Adjustable Trip Setting Current Range Per Pole In Amps: +2500.0/+5000.0 ac all locations **Trip Release Ambient Tempurature Rating:** 40.0 degrees celsius all locations **Special Features:** Load lugs included **Frequency In Hertz:** 60.0 all locations **Terminal Type And Quantity:** 

6 compression

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0