NSN 5925-01-332-3264

Circuit Breaker - Page 1 of 2

Overcurrent all locations



View Online at https://aerobasegroup.com/nsn/5925-01-332-3264

Body Style:
Multipole-single actuator type
Body Length:
6.023 inches
Body Width:
4.126 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
2.250 inches
Center To Center Distance Between Terminals Parallel To Width:
0.688 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
4.500 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.688 inches
Fragility Factor:
Moderately rugged
Boss Height:
0.125 inches
Mounting Surface To Terminal End Distance:
3.375 inches
Pole Quantity:
2
Arc Quenching Method:
Deion
Mounting Facility Type And Quantity:
4 threaded hole
Storage Type:
General purpose warehouse
Special Handling Feature:
Magnetic
Thready Qty Per Inch (tpi):
32
Maximum Continuous Load Current Rating Per Pole:
100.0 amperes ac all locations and 100.0 amperes dc all locations
Operating Voltage Type And Rating Per Pole In Volts:
480.0 ac all locations and 250.0 dc all locations
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
14000.0 ac all locations and 10000.0 dc all locations
Circuit Protection Type:

NSN 5925-01-332-3264

Circuit Breaker - Page 2 of 2



Trip Release Method:
Thermal-magnetic all locations
Trip Release Characteristic:
Instantaneous all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
2 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At each pole
External Actuator Linkage Arrangement:
One and two linked
Thread Size:
0.164 inches
Inclosure Protection Type For Which Designed:
Fungus resistant and moisture resistant
Trip Release Ambient Tempurature Rating:
40.0 degrees celsius all locations
Frequency In Hertz:
50.0 all locations or 60.0 all locations
Thread Series Designator:
Unc
Terminal Type And Quantity:
4 threaded stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0