

View Online at <https://aerobasegroup.com/nsn/5925-01-332-9927>

**Body Style:**

Multipole-single actuator type

**Bushing Length:**

Between 0.332 inches and 0.380 inches

**Body Length:**

1.562 inches

**Body Width:**

1.281 inches

**Case Material:**

Metal

**Center To Center Distance Between Terminals Parallel To Length:**

0.906 inches

**Center To Center Distance Between Terminals Parallel To Width:**

Between 0.927 inches and 0.947 inches

**Nonturn Device Location:**

At 3 oclock and at 9 oclock

**Nonturn Device Radius:**

Between 0.581 inches and 0.701 inches

**Fragility Factor:**

Moderately rugged

**Mounting Surface To Terminal End Distance:**

1.828 inches

**Pole Quantity:**

2

**Arc Quenching Method:**

Magnetic blowout

**Mounting Facility Type And Quantity:**

1 threaded bushing w/panel seal

**Storage Type:**

General purpose warehouse

**Special Handling Feature:**

Magnetic

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

7.5 amperes dc first location

**Operating Voltage Type And Rating Per Pole In Volts:**

28.0 dc all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

500.0 dc all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

115.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

Between pole one and two

**Internal Trip Release Configuration:**

Series trip all locations

**Thread Size:**

0.375 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

0.055 at 200 pct all locations and 0.950 at 200 pct all locations

**Inclosure Protection Type For Which Designed:**

Vibration resistant and shockproof and moisture resistant and salt spray proof

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

4 wire hook

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0