## NSN 5925-01-336-7208



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-01-336-7208 **Body Style:** Multipole-multiple actuator type **Body Length:** 2.000 inches **Body Width:** 1.515 inches **Case Material:** Plastic **Center To Center Distance Between Terminals Parallel To Length:** 1.560 inches **Center To Center Distance Between Terminals Parallel To Width:** 0.750 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.660 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.750 inches **Fragility Factor:** Moderately rugged **Boss Height:** 0.240 inches **Mounting Surface To Terminal End Distance:** 2.122 inches **Pole Quantity: Mounting Facility Type And Quantity:** 4 threaded hole Storage Type: General purpose warehouse **Maximum Continuous Load Current Rating Per Pole:** 30.0 amperes ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Magnetic all locations

**Trip Release Characteristic:** 

Time delay all locations

**Reset Method:** 

Manual

**Main Contact Tripping Mechanism Type:** 

Trip free

**Manual Actuator Type And Quantity:** 

2 toggle

## NSN 5925-01-336-7208

Circuit Breaker - Page 2 of 2



Actuator Function:
Trip-reset
Actuator Position Designation:
Between pole one and two
Internal Trip Release Configuration:
Series trip all locations
Thread Size:
0.195 inches
Inclosure Protection Type For Which Designed:
Shockproof and vibrationproof and moisture resistant
Thread Series Designator:
Unc
Terminal Type And Quantity:
4 tab w/screw
Shelf Life:
N/a
Unit Of Measure:
<del>.</del>
Demilitarization:
No
Fiig:
A030a0