

View Online at <https://aerobasegroup.com/nsn/5925-01-337-0286>

**Body Style:**

Multipole-single actuator type

**Body Length:**

10.000 inches

**Body Width:**

4.125 inches

**Body Height:**

4.062 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

9.000 inches

**Center To Center Distance Between Terminals Parallel To Width:**

1.375 inches

**Unthreaded Mounting Hole Diameter:**

0.250 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

7.250 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.375 inches

**Fragility Factor:**

Moderately rugged

**Boss Height:**

0.250 inches

**Pole Quantity:**

3

**Arc Quenching Method:**

Magnetic blowout

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Storage Type:**

General purpose warehouse

**Special Handling Feature:**

Magnetic

**Features Provided:**

Adjustable trip release

**Cubic Measure:**

101.970 cubic inches

**Maximum Continuous Load Current Rating Per Pole:**

150.0 amperes ac all locations and 150.0 amperes dc all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

600.0 ac all locations and 250.0 dc all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

25000.0 ac all locations and 10000.0 dc all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Instantaneous all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole two

**Adjustable Trip Setting Current Range Per Pole In Amps:**

+750.0/+2500.0 ac all locations

**Internal Trip Release Configuration:**

Series trip all locations

**Inclosure Protection Type For Which Designed:**

General purpose

**Frequency In Hertz:**

60.0 all locations

**Terminal Type And Quantity:**

6 compression

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0