NSN 5925-01-338-6852

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-338-6852

Body Style:
Rectangular dimensional envelope
Overall Length:
22.520 inches
Overall Height:
5.190 inches
Overall Width:
8.250 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.312 inches
Fragility Factor:
Moderately rugged
Pole Quantity:
3
Arc Quenching Method:
Magnetic blowout
Mounting Facility Type And Quantity:
4 unthreaded hole
Storage Type:
General purpose warehouse
Special Handling Feature:
Magnetic
Features Provided:
Adjustable trip release
Maximum Continuous Load Current Rating Per Pole:
150.0 amperes ac all locations
Operating Voltage Type And Rating Per Pole In Volts:
480.0 ac all locations
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
100000.0 ac all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Thermal-magnetic all locations
Trip Release Characteristic:
Instantaneous all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 all locations

Manual

Reset Method:

NSN 5925-01-338-6852 Circuit Breaker - Page 2 of 2



Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Adjustable Trip Setting Current Range Per Pole In Amps:
+750.0/+1500.0 ac all locations
Inclosure Protection Type For Which Designed:
General purpose
Trip Release Ambient Tempurature Rating:
25.0 degrees celsius all locations
Frequency In Hertz:
50.0 all locations or 60.0 all locations
Terminal Type And Quantity:
6 compression
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0