## NSN 5925-01-339-4014

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-339-4014 **Body Style:** Rectangular dimensional envelope **Overall Length:** 3.281 inches **Overall Height:** 1.000 inches **Overall Width:** 2.375 inches **Case Material: Plastic Fragility Factor:** Moderately rugged **Pole Quantity: Arc Quenching Method:** Magnetic blowout **Mounting Facility Type And Quantity:** 2 clip Storage Type: General purpose warehouse **Special Handling Feature:** Magnetic **Maximum Continuous Load Current Rating Per Pole:** 20.0 amperes ac single location **Operating Voltage Type And Rating Per Pole In Volts:** 240.0 ac single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 10000.0 ac single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Magnetic single location **Trip Release Characteristic:** Instantaneous single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 single location **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free

1 toggle

**Manual Actuator Type And Quantity:** 

## NSN 5925-01-339-4014

Circuit Breaker - Page 2 of 2



Actuator Function:
Trip-reset
Actuator Position Designation:
At pole one
Internal Trip Release Configuration:
Series trip single location
Inclosure Protection Type For Which Designed:
Dustproof
Frequency In Hertz:
60.0 single location
Terminal Type And Quantity:
2 bus bar
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
Δ030a0