

View Online at <https://aerobasegroup.com/nsn/5925-01-344-7488>

Body Style:

Multipole-multiple actuator type

Bushing Length:

Between 0.235 inches and 0.250 inches

Body Length:

2.200 inches

Body Width:

2.270 inches

Case Material:

Metal

Center To Center Distance Between Terminals Parallel To Length:

1.190 inches

Center To Center Distance Between Terminals Parallel To Width:

1.500 inches

Fragility Factor:

Moderately rugged

Mounting Surface To Terminal End Distance:

2.370 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

6 threaded hole

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

5.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

120.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

138.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push button

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Thread Size:

0.138 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

10.000 at 200 pct all locations and 70.000 at 200 pct all locations

Inclosure Protection Type For Which Designed:

Corrosion resistant and humidity resistant and shock resistant and hermetically sealed

Trip Release Ambient Temperature Rating:

77.0 degrees fahrenheit all locations

Frequency In Hertz:

400.0 all locations

Unpackaged Unit Weight:

0.650 pounds

Thread Series Designator:

Unc

Terminal Type And Quantity:

6 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0