NSN 5925-01-344-7489

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-344-7489

Body Style:

Multipole-multiple actuator type

Bushing Length:

Between 0.235 inches and 0.250 inches

Body Length:

2.200 inches

Body Width:

2.270 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.190 inches

Center To Center Distance Between Terminals Parallel To Width:

1.500 inches

Fragility Factor:

Moderately rugged

Mounting Surface To Terminal End Distance:

2.370 inches

Pole Quantity:

Mounting Facility Type And Quantity:

6 threaded hole

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Thready Qty Per Inch (tpi):

Maximum Continuous Load Current Rating Per Pole:

50.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

120.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

138.0 all locations

NSN 5925-01-344-7489

Circuit Breaker - Page 2 of 2



Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 push button
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Thread Size:
0.138 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
10.000 at 200 pct all locations and 70.000 at 200 pct all locations
Inclosure Protection Type For Which Designed:
Corrosion resistant and humidity resistant and shock resistant
Trip Release Ambient Tempurature Rating:
77.0 degrees fahrenheit all locations
Frequency In Hertz:
400.0 all locations
Unpackaged Unit Weight:
0.650 pounds
Thread Series Designator:
Unc
Terminal Type And Quantity:
6 tab w/screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0