NSN 5925-01-345-0992

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-345-0992

# Body Style:

Multipole-single actuator type

# **Bushing Length:**

0.318 inches

# Body Length:

2.200 inches

## Body Width:

2.270 inches

## **Body Height:**

2.470 inches

Case Material:

## Metal

Center To Center Distance Between Terminals Parallel To Length:

## 1.190 inches

Center To Center Distance Between Terminals Parallel To Width:

#### 0.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 1.800 inches and 1.820 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.750 inches

## **Fragility Factor:**

Moderately rugged

## Pole Quantity:

3

# Mounting Facility Type And Quantity:

6 threaded hole

# Storage Type:

General purpose warehouse

# Special Handling Feature:

Magnetic

# Thready Qty Per Inch (tpi):

32

# Maximum Continuous Load Current Rating Per Pole:

30.0 amperes ac all locations

# Operating Voltage Type And Rating Per Pole In Volts:

120.0 ac all locations

# Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac all locations

# Circuit Protection Type:

Overcurrent all locations

## Trip Release Method:

Thermal-magnetic all locations

# NSN 5925-01-345-0992

Circuit Breaker - Page 2 of 2



### **Trip Release Characteristic:**

Time delay all locations

### Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

140.0 all locations

## **Reset Method:**

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push-pull

**Actuator Function:** 

Trip-reset

#### **Actuator Position Designation:**

At pole two

## Thread Size:

0.138 inches

#### Trip Delay Time In Seconds Per Rated Continuous Current:

10.000 at 200 pct all locations and 70.000 at 200 pct all locations

## Inclosure Protection Type For Which Designed:

Corrosion resistant and humidity resistant and shock resistant and hermetically sealed

## Trip Release Ambient Tempurature Rating:

25.0 degrees celsius all locations

Frequency In Hertz:

400.0 all locations

## **Unpackaged Unit Weight:**

0.650 pounds

## **Thread Series Designator:**

Unc

## Terminal Type And Quantity:

6 tab w/screw

Shelf Life:

N/a

#### Unit Of Measure:

---

#### **Demilitarization:**

No

Fiig:

A030a0