NSN 5925-01-346-6171

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-346-6171 **Body Style:** Rectangular dimensional envelope **Overall Length:** 6.344 inches **Overall Height:** 3.000 inches **Overall Width:** 4.406 inches **Case Material: Plastic Unthreaded Mounting Hole Diameter:** 0.196 inches **Fragility Factor:** Moderately rugged **Pole Quantity: Arc Quenching Method:** Magnetic blowout **Mounting Facility Type And Quantity:** 4 unthreaded hole Storage Type: General purpose warehouse **Special Handling Feature:** Magnetic **Maximum Continuous Load Current Rating Per Pole:** 25.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 480.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 18000.0 ac all locations **Circuit Protection Type:** Overvoltage all locations **Trip Release Method:** Thermal all locations **Trip Release Characteristic:** Instantaneous all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 all locations **Reset Method:**

Manual

Main Contact Tripping Mechanism Type:

Trip free

NSN 5925-01-346-6171

Circuit Breaker - Page 2 of 2



Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Internal Trip Release Configuration:
Series trip all locations
Inclosure Protection Type For Which Designed:
Dustproof and fungus proof
Trip Release Ambient Tempurature Rating:
50.0 degrees celsius all locations
Frequency In Hertz:
60.0 all locations
Terminal Type And Quantity:
6 compression
Shelf Life:
N/a
Unit Of Measure:
.
Demilitarization:
No
Fiig:
A030a0