

View Online at <https://aerobasegroup.com/nsn/5925-01-346-7535>

Body Style:

Rectangular dimensional envelope

Overall Length:

7.000 inches

Overall Height:

2.531 inches

Overall Width:

3.000 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.196 inches

Fragility Factor:

Moderately rugged

Pole Quantity:

2

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

2 unthreaded hole

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Maximum Continuous Load Current Rating Per Pole:

150.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

10000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Instantaneous all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Series trip all locations

Inclosure Protection Type For Which Designed:

Dustproof and fungus proof

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

4 compression

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0