

View Online at <https://aerobasegroup.com/nsn/5925-01-346-7536>

Body Style:

Rectangular dimensional envelope

Overall Length:

3.750 inches

Overall Height:

2.000 inches

Overall Width:

2.375 inches

Case Material:

Plastic

Fragility Factor:

Moderately rugged

Pole Quantity:

2

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

2 clip and 2 terminal

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Maximum Continuous Load Current Rating Per Pole:

30.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

10000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Instantaneous all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

2 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At each pole

External Actuator Linkage Arrangement:

One and two linked

Internal Trip Release Configuration:

Series trip all locations

Inclosure Protection Type For Which Designed:

Dustproof and fungus proof

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

2 compression and 2 clip

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0