NSN 5925-01-347-2052

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-347-2052

Body Style:
Multipole-single actuator type
Bushing Length:
Between 0.332 inches and 0.380 inches
Body Length:
2.500 inches
Body Width:
1.281 inches
Case Material:
Metal
Center To Center Distance Between Terminals Parallel To Length:
0.906 inches
Center To Center Distance Between Terminals Parallel To Width:
Between 0.594 inches and 0.656 inches
Fragility Factor:
Moderately rugged
Mounting Surface To Terminal End Distance:
1.828 inches
Pole Quantity:
2
Arc Quenching Method:
Magnetic blowout
Mounting Facility Type And Quantity:
1 threaded bushing w/panel seal
Storage Type:
General purpose warehouse
Special Handling Feature:
Magnetic
Maximum Continuous Load Current Rating Per Pole:
3.0 amperes ac first location3.0 amperes dc second location
Operating Voltage Type And Rating Per Pole In Volts:
240.0 ac first location50.0 dc second location
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
300.0 ac first location500.0 dc second location
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Magnetic all locations
Trip Release Characteristic:
Time delay all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

150.0 all locations

NSN 5925-01-347-2052 Circuit Breaker - Page 2 of 2



Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
Between pole one and two
Internal Trip Release Configuration:
Series trip all locations
Thread Size:
0.375 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
0.800 at 200 pct all locations and 8.500 at 200 pct all locations
Inclosure Protection Type For Which Designed:
Hermetically sealed and dustproof
Frequency In Hertz:
400.0 first location
Thread Series Designator:
Unef
Terminal Type And Quantity:
4 wire hook
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A030a0