# NSN 5925-01-348-0346

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-348-0346

## **Body Style:**

Multipole-single actuator type

## **Bushing Length:**

Between 0.332 inches and 0.380 inches

## **Body Length:**

1.562 inches

#### **Body Width:**

1.281 inches

#### **Case Material:**

Metal

## Center To Center Distance Between Terminals Parallel To Length:

#### 0.906 inches

Center To Center Distance Between Terminals Parallel To Width:

0.625 inches

Mounting Surface To Terminal End Distance:

# 1.828 inches

**Pole Quantity:** 

2

Mounting Facility Type And Quantity:

1 threaded bushing w/panel seal

## Maximum Continuous Load Current Rating Per Pole:

8.0 amperes ac all locations and 8.0 amperes dc all locations

## **Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac all locations and 50.0 dc all locations

## Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

300.0 ac all locations and 500.0 dc all locations

## **Circuit Protection Type:**

Overcurrent all locations

## Trip Release Method:

Magnetic all locations

## **Trip Release Characteristic:**

Time delay all locations

## Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

150.0 all locations

#### **Reset Method:**

Manual

## Main Contact Tripping Mechanism Type:

Trip free

## Manual Actuator Type And Quantity:

1 toggle

## **Actuator Function:**

Trip-reset

# NSN 5925-01-348-0346

Circuit Breaker - Page 2 of 2



#### **Actuator Position Designation:**

Between pole one and two

Internal Trip Release Configuration:

Series trip all locations

## Thread Size:

0.375 inches

## Trip Delay Time In Seconds Per Rated Continuous Current:

0.180 at 200 pct all locations and 1.180 at 200 pct all locations

#### **Frequency In Hertz:**

400.0 all locations

#### **Test Data Document:**

81349-mil-c-39019 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Thread Series Designator:**

Unef

#### **Terminal Type And Quantity:**

4 wire hook

#### **Specification Data:**

81349-mil-39019/3 government specification

Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

# Fiig:

A030a0