

View Online at <https://aerobasegroup.com/nsn/5925-01-349-5601>

Body Style:

Multipole-single actuator type

Body Length:

6.310 inches

Body Width:

4.120 inches

Body Height:

3.380 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

4.880 inches

Center To Center Distance Between Terminals Parallel To Width:

1.000 inches

Unthreaded Mounting Hole Diameter:

0.196 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

4.880 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.500 inches

Boss Height:

0.710 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

4 unthreaded hole

Maximum Continuous Load Current Rating Per Pole:

10.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

480.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

14000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Instantaneous all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Internal Trip Release Configuration:

Series trip all locations

Special Features:

Includes mounting base 1, shunt trip device 1

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

6 compression

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0