

View Online at <https://aerobasegroup.com/nsn/5925-01-349-6777>

Case Material:

Plastic

Fragility Factor:

Moderately rugged

Pole Quantity:

3

Storage Type:

General purpose warehouse

Operating Voltage Type And Rating Per Pole In Volts:

500.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

135.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Internal Trip Release Configuration:

Series trip all locations

Trip Delay Time In Seconds Per Rated Continuous Current:

20.000 at 200 pct all locations and 32.000 at 200 pct all locations

Inclosure Protection Type For Which Designed:

Shock resistant and vibration resistant

Trip Release Ambient Temperature Rating:

50.0 degrees celsius all locations

Frequency In Hertz:

60.0 all locations

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0