

View Online at <https://aerobasegroup.com/nsn/5925-01-350-0674>

Body Style:

Rectangular dimensional envelope

Overall Length:

6.220 inches

Overall Height:

4.120 inches

Overall Width:

4.360 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.196 inches

Fragility Factor:

Moderately rugged

Pole Quantity:

3

Mounting Facility Type And Quantity:

6 unthreaded hole

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Maximum Continuous Load Current Rating Per Pole:

70.0 amperes ac all locations and 70.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

120.0 ac all locations and 125.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

14000.0 ac all locations and 5000.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Instantaneous all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Trip Release Ambient Temperature Rating:

50.0 degrees celsius all locations

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

6 compression

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0