NSN 5925-01-350-1846

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-350-1846 **Body Style:** Multipole-single actuator type **Body Length:** 6.310 inches **Body Width: 4.120 inches Body Height:** 3.380 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length:** 4.880 inches **Center To Center Distance Between Terminals Parallel To Width:** 1.380 inches **Unthreaded Mounting Hole Diameter:** 0.188 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 3.380 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.380 inches **Fragility Factor:** Moderately rugged **Boss Height:** 0.710 inches **Pole Quantity:** 3 **Mounting Facility Type And Quantity:** 4 unthreaded hole Storage Type: General purpose warehouse **Special Handling Feature:** Magnetic **Maximum Continuous Load Current Rating Per Pole:** 150.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 600.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 18000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations

Trip Release Method:

Magnetic all locations

NSN 5925-01-350-1846 Circuit Breaker - Page 2 of 2



Trip Release Characteristic:
Instantaneous all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Internal Trip Release Configuration:
Series trip all locations
Inclosure Protection Type For Which Designed:
Fungus resistant and moisture resistant
Frequency In Hertz:
60.0 all locations
Terminal Type And Quantity:
6 compression
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0