

View Online at <https://aerobasegroup.com/nsn/5925-01-350-5383>

**Case Material:**

Plastic

**Pole Quantity:**

3

**Features Provided:**

Adjustable trip release

**Maximum Continuous Load Current Rating Per Pole:**

800.0 amperes ac all locations and 800.0 amperes dc all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

600.0 ac all locations and 250.0 dc all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

30000.0 ac all locations and 30000.0 dc all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal-magnetic all locations

**Auxiliary Trip Coil Voltage Type And Rating In Volts:**

120.0 ac all locations

**Trip Release Characteristic:**

Instantaneous all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole two

**Adjustable Trip Setting Current Range Per Pole In Amps:**

+4000.0/+6400.0 ac all locations

**Trip Release Duty Cycle:**

Continuous all locations

**Inclosure Protection Type For Which Designed:**

Dustproof and fungus proof

**Trip Release Ambient Temperature Rating:**

50.0 degrees celsius all locations

**Frequency In Hertz:**

60.0 all locations

**Terminal Type And Quantity:**

6 compression

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0