## NSN 5925-01-350-9830



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-01-350-9830 **Body Style:** Single pole type **Body Length:** 2.000 inches **Body Width:** 0.755 inches **Case Material:** Plastic **Center To Center Distance Between Terminals Parallel To Length:** 1.560 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.660 inches **Switch Contact Arrangement:** Single pole, double throw **Fragility Factor:** Moderately rugged **Boss Height:** 0.130 inches **Mounting Surface To Terminal End Distance:** 1.640 inches **Pole Quantity:** 1 **Mounting Facility Type And Quantity:** 2 threaded hole Storage Type: General purpose warehouse **Special Handling Feature:** Magnetic Thready Qty Per Inch (tpi): 32 **Maximum Continuous Load Current Rating Per Pole:** 30.0 amperes dc single location **Operating Voltage Type And Rating Per Pole In Volts:** 

32.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

2500.0 dc single location

**Circuit Protection Type:** 

Overcurrent single location

**Trip Release Method:** 

Magnetic single location

**Trip Release Characteristic:** 

Time delay single location

## **NSN 5925-01-350-9830** Circuit Breaker - Page 2 of 2



Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 single location
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole one
Internal Trip Release Configuration:
Series trip single location
Thread Size:
0.138 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
0.150 at 200 pct single location and 1.500 at 200 pct single location
Inclosure Protection Type For Which Designed:
Shock resistant and vibration resistant and moisture resistant and salt spray proof
Switch Terminal Type:
Quick disconnect, male
Switch Current Rating And Type In Amps:
10.0 ac and 5.0 dc
Switch Voltage Rating And Type In Volts:
250.0 ac and 30.0 dc
Unpackaged Unit Weight:
65.0 grams
Thread Series Designator:
Unc
Terminal Type And Quantity:
2 quick disconnect, male
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0