

View Online at <https://aerobasegroup.com/nsn/5925-01-351-2873>

**Body Style:**

Single pole type

**Bushing Length:**

0.500 inches

**Body Length:**

1.380 inches

**Body Width:**

0.560 inches

**Case Material:**

Metal

**Center To Center Distance Between Terminals Parallel To Length:**

0.840 inches

**End Application:**

2320-01-304-2277 pls (palletized loading system)

**Mounting Surface To Terminal End Distance:**

1.660 inches

**Pole Quantity:**

1

**Mounting Facility Type And Quantity:**

1 threaded bushing w/panel seal

**Thready Qty Per Inch (tpi):**

28

**Maximum Continuous Load Current Rating Per Pole:**

30.0 amperes ac single location and 30.0 amperes dc single location

**Operating Voltage Type And Rating Per Pole In Volts:**

250.0 ac single location and 50.0 dc single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

1000.0 ac single location and 1000.0 dc single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Magnetic single location

**Trip Release Characteristic:**

Instantaneous single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

138.0 single location

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 push button

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole one

**Internal Trip Release Configuration:**

Series trip single location

**Thread Size:**

0.440 inches

**Frequency In Hertz:**

60.0 single location

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

1 screw and 1 quick disconnect, male

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0