

View Online at <https://aerobasegroup.com/nsn/5925-01-352-6727>

**Body Style:**

Multipole-multiple actuator type

**Body Length:**

2.000 inches

**Body Width:**

2.250 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

1.560 inches

**Center To Center Distance Between Terminals Parallel To Width:**

0.750 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

1.660 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.750 inches

**Boss Height:**

0.140 inches

**Mounting Surface To Terminal End Distance:**

2.032 inches

**Pole Quantity:**

2

**Mounting Facility Type And Quantity:**

6 threaded hole

**Maximum Continuous Load Current Rating Per Pole:**

25.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

1000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

3 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At each pole

**Internal Trip Release Configuration:**

Series trip all locations

**Thread Size:**

0.136 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

10.000 at 200 pct all locations and 108.000 at 200 pct all locations

**Frequency In Hertz:**

50.0 all locations or 60.0 all locations

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

6 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0