NSN 5925-01-353-1388



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-01-353-1388 **Body Style:** Rectangular dimensional envelope **Overall Length:** 4.125 inches **Overall Height:** 0.750 inches **Overall Width:** 3.125 inches **Case Material: Plastic Fragility Factor:** Moderately rugged **Pole Quantity: Mounting Facility Type And Quantity:** 4 clamp Storage Type: General purpose warehouse **Special Handling Feature:** Magnetic **Maximum Continuous Load Current Rating Per Pole:** 30.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 480.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 25000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Thermal-magnetic all locations **Trip Release Characteristic:** Instantaneous all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 138.0 all locations **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 1 toggle

Actuator Function:

Trip-reset

NSN 5925-01-353-1388

Circuit Breaker - Page 2 of 2



| Actuator Position Designation: |
|---|
| At pole one |
| Inclosure Protection Type For Which Designed: |
| General purpose |
| Trip Release Ambient Tempurature Rating: |
| 25.0 degrees celsius all locations |
| Frequency In Hertz: |
| 60.0 all locations |
| Unpackaged Unit Weight: |
| 24.000 pounds |
| Terminal Type And Quantity: |
| 4 compression |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A030a0