

View Online at <https://aerobasegroup.com/nsn/5925-01-353-6912>

Body Style:

Single pole type

Bushing Length:

0.625 inches

Body Length:

2.000 inches

Body Width:

0.750 inches

Case Material:

Metal

Center To Center Distance Between Terminals Parallel To Length:

1.530 inches

Switch Contact Arrangement:

Single pole, double throw

Mounting Surface To Terminal End Distance:

2.232 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

1 threaded bushing w/panel seal

Maximum Continuous Load Current Rating Per Pole:

30.0 amperes ac all locations and 30.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac all locations and 50.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

300.0 ac all locations and 500.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Instantaneous all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Auxiliary Switch Function And Quantity:

1 alarm

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.375 inches

Switch Location And Position Designation:

Internal at pole one

Switch Terminal Type:

Tab, solder lug

Frequency In Hertz:

60.0 all locations

Test Data Document:

81349-mil-c-55629 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Terminal Type And Quantity:

2 wire hook

Specification Data:

81349-mil-c-55629/20 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0