

View Online at <https://aerobasegroup.com/nsn/5925-01-354-6094>

**Body Style:**

Multipole-multiple actuator type

**Body Length:**

2.000 inches

**Body Width:**

1.515 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

1.530 inches

**Center To Center Distance Between Terminals Parallel To Width:**

0.750 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

1.660 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.750 inches

**Fragility Factor:**

Moderately rugged

**Boss Height:**

0.130 inches

**Mounting Surface To Terminal End Distance:**

2.032 inches

**Pole Quantity:**

2

**Mounting Facility Type And Quantity:**

4 threaded hole

**Storage Type:**

General purpose warehouse

**Special Handling Feature:**

Magnetic

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

50.0 amperes dc all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

32.0 dc all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

1500.0 dc all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

2 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At each pole

**External Actuator Linkage Arrangement:**

One and two linked

**Internal Trip Release Configuration:**

Series trip all locations

**Thread Size:**

0.138 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

0.100 at 200 pct all locations and 1.200 at 200 pct all locations

**Inclosure Protection Type For Which Designed:**

Corrosion resistant and moisture resistant and shockproof and vibrationproof

**Unpackaged Unit Weight:**

4.400 ounces

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

4 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0