NSN 5925-01-354-9720

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-354-9720 **Body Style:** Single pole type **Body Length:** 2.490 inches **Body Width:** 0.750 inches **Case Material:** Plastic **Center To Center Distance Between Terminals Parallel To Length:** 1.940 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** 2.060 inches **Boss Height:** 0.150 inches **Mounting Surface To Terminal End Distance:** 2.625 inches **Pole Quantity: Mounting Facility Type And Quantity:** 2 threaded hole **Maximum Continuous Load Current Rating Per Pole:** 50.0 amperes dc single location **Operating Voltage Type And Rating Per Pole In Volts:** 32.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 2000.0 dc single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Magnetic single location **Trip Release Characteristic:** Time delay single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 115.0 single location **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 1 toggle

Trip-reset

Actuator Function:

NSN 5925-01-354-9720

Circuit Breaker - Page 2 of 2



Actuator Position Designation:	
At pole one	
Internal Trip Release Configuration:	
Series trip single location	
Thread Size:	
0.138 inches	
Trip Delay Time In Seconds Per Rated Continuous Current:	
0.100 at 200 pct single location and 1.700 at 200 pct single location	
Thread Series Designator:	
Unc	
Terminal Type And Quantity:	
2 threaded stud	
Shelf Life:	
N/a	
Unit Of Measure:	
.	
Demilitarization:	
No	
Fiig:	
A030a0	