

View Online at <https://aerobasegroup.com/nsn/5925-01-355-5351>

Body Style:

Multipole-single actuator type

Body Length:

2.000 inches

Body Width:

1.540 inches

Body Height:

1.770 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.250 inches

Center To Center Distance Between Terminals Parallel To Width:

0.625 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 1.250 inches and 1.260 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.625 inches

Fragility Factor:

Moderately rugged

Boss Height:

0.125 inches

Pole Quantity:

2

Mounting Facility Type And Quantity:

4 clip

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Maximum Continuous Load Current Rating Per Pole:

5.0 amperes ac all locations and 5.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac all locations and 50.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

2000.0 ac all locations and 1000.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

Between pole one and two

Internal Trip Release Configuration:

Series trip all locations

Trip Delay Time In Seconds Per Rated Continuous Current:

3.000 at 200 pct all locations and 30.000 at 200 pct all locations

Inclosure Protection Type For Which Designed:

Shock resistant and vibration resistant

Special Features:

Handle is illuminated with a green glow

Frequency In Hertz:

50.0 all locations or 60.0 all locations

Unpackaged Unit Weight:

2.600 ounces

Terminal Type And Quantity:

4 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0