

View Online at <https://aerobasegroup.com/nsn/5925-01-356-8572>

**Body Style:**

Multipole-single actuator type

**Bushing Length:**

0.150 inches

**Body Length:**

2.189 inches

**Body Width:**

1.530 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

1.190 inches

**Center To Center Distance Between Terminals Parallel To Width:**

0.750 inches

**Mounting Surface To Terminal End Distance:**

2.180 inches

**Pole Quantity:**

2

**Mounting Facility Type And Quantity:**

4 threaded hole

**Maximum Continuous Load Current Rating Per Pole:**

20.0 amperes ac all locations and 20.0 amperes dc all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

205.0 ac all locations and 30.0 dc all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

4200.0 ac all locations and 1000.0 dc all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 push button

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

Between pole one and two

**Internal Trip Release Configuration:**

Series trip all locations

**Thread Size:**

0.168 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

12.000 at 200 pct all locations and 65.000 at 200 pct all locations

**Frequency In Hertz:**

400.0 all locations

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

4 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0