

View Online at <https://aerobasegroup.com/nsn/5925-01-357-1308>

Body Style:

Single pole type

Body Length:

2.500 inches

Body Width:

0.750 inches

Body Height:

1.841 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.660 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

0.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

2.062 inches

End Application:

Afscn/cue; automated remote tracking station (arts)

Boss Height:

0.750 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 threaded hole

Maximum Continuous Load Current Rating Per Pole:

15.0 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

480.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

0.180 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Nontrip free

Internal Trip Release Configuration:

Series trip single location

Thread Size:

0.138 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

0.120 at 150 pct single location

Inclosure Protection Type For Which Designed:

General purpose

Criticality Code Justification:

Feat

Special Features:

Weapon system essential

Frequency In Hertz:

60.0 single location

Thread Series Designator:

Unc

Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A030a0