

View Online at <https://aerobasegroup.com/nsn/5925-01-357-4268>

Body Style:

Rectangular dimensional envelope

Overall Length:

3.150 inches

Overall Height:

0.450 inches

Overall Width:

2.080 inches

Case Material:

Plastic

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 threaded hole

Maximum Continuous Load Current Rating Per Pole:

10.0 amperes ac single location and 10.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac single location and 65.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac single location and 1000.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal-magnetic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push button

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Trip Release Ambient Temperature Rating:

25.0 degrees celsius single location

Frequency In Hertz:

60.0 single location

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0