NSN 5925-01-357-5559

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-357-5559 **Body Style:** Multipole-single actuator type **Bushing Length:** 0.250 inches **Body Length:** 2.063 inches **Body Width:** 1.300 inches **Body Height:** 1.875 inches **Case Material:** Ceramic Center To Center Distance Between Terminals Parallel To Length: 0.688 inches **Center To Center Distance Between Terminals Parallel To Width:** 0.750 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.376 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.750 inches **Fragility Factor:** Moderately rugged **Pole Quantity: Mounting Facility Type And Quantity:** 1 threaded stud Storage Type: General purpose warehouse **Special Handling Feature:** Magnetic Thready Qty Per Inch (tpi): **Maximum Continuous Load Current Rating Per Pole:** 3.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 205.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 1000.0 ac all locations

Circuit Protection Type: Overcurrent all locations

Trip Release Method:

Magnetic all locations

NSN 5925-01-357-5559 Circuit Breaker - Page 2 of 2



Trip Release Characteristic:
Time delay all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 push-pull
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Internal Trip Release Configuration:
Series trip all locations
Thread Size:
0.469 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
0.700 at 200 pct all locations and 3.300 at 200 pct all locations
Inclosure Protection Type For Which Designed:
General purpose
Frequency In Hertz:
400.0 all locations
Precious Material And Location:
Contact surfaces silver
Precious Material:
Silver
Thread Series Designator:
Unc
Terminal Type And Quantity:
6 threaded stud
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A030a0