

View Online at <https://aerobasegroup.com/nsn/5925-01-358-8432>

**Case Material:**

Plastic

**End Application:**

An/mpn-14k

**Pole Quantity:**

3

**Maximum Continuous Load Current Rating Per Pole:**

125.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

18000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Auxiliary Trip Coil Voltage Type And Rating In Volts:**

28.0 dc third location

**Trip Release Characteristic:**

Instantaneous all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Auxiliary Switch Function And Quantity:**

1 alarm

**Internal Trip Release Configuration:**

Series/relay trip third location

**Trip Release Duty Cycle:**

Continuous third location

**Frequency In Hertz:**

60.0 all locations

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0