NSN 5925-01-361-4275

Circuit Breaker - Page 1 of 2

Body Style:

Trip free



View Online at https://aerobasegroup.com/nsn/5925-01-361-4275

Multipole-multiple actuator type
Body Length:
2.490 inches
Body Width:
2.265 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
1.940 inches
Center To Center Distance Between Terminals Parallel To Width:
0.750 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
2.060 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.750 inches
Boss Height:
0.150 inches
Mounting Surface To Terminal End Distance:
2.625 inches
Pole Quantity:
3
Mounting Facility Type And Quantity:
6 threaded hole
Maximum Continuous Load Current Rating Per Pole:
0.8 amperes ac all locations
Operating Voltage Type And Rating Per Pole In Volts:
480.0 ac all locations
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
1500.0 ac all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Magnetic all locations
Trip Release Characteristic:
Time delay all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
115.0 all locations
115.0 all locations Reset Method:

NSN 5925-01-361-4275

Circuit Breaker - Page 2 of 2



Manual Actuator Type And Quantity:
3 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At each pole
External Actuator Linkage Arrangement:
One, two, and three linked
Internal Trip Release Configuration:
Series trip all locations
Thread Size:
0.138 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
2.000 at 200 pct all locations and 22.000 at 200 pct all locations
Frequency In Hertz:
50.0 all locations or 60.0 all locations
Thread Series Designator:
Unc
Terminal Type And Quantity:
6 threaded stud
Shelf Life:
N/a
Unit Of Measure:
.
Demilitarization:
No
Fiig:
A030a0