

View Online at <https://aerobasegroup.com/nsn/5925-01-361-5434>

Body Style:

Rectangular dimensional envelope

Overall Length:

108.0 millimeters

Overall Height:

70.0 millimeters

Overall Width:

81.0 millimeters

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

18.0 millimeters

Fragility Factor:

Moderately rugged

Pole Quantity:

4

Mounting Facility Type And Quantity:

8 unthreaded hole

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Maximum Continuous Load Current Rating Per Pole:

63.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

50.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

20000.0 ac single location

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Instantaneous all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

4 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At each pole

External Actuator Linkage Arrangement:

One, two, three, and four linked

Inclosure Protection Type For Which Designed:

General purpose

Trip Release Ambient Temperature Rating:

25.0 degrees celsius all locations

Frequency In Hertz:

50.0 all locations

Terminal Type And Quantity:

8 compression

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0