## NSN 5925-01-361-5511



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-01-361-5511 **Body Style:** Multipole-single actuator type **Bushing Length:** 0.380 inches **Body Length:** 1.562 inches **Body Width:** 1.281 inches **Case Material:** Metal **Center To Center Distance Between Terminals Parallel To Length:** 0.875 inches **Center To Center Distance Between Terminals Parallel To Width:** 0.625 inches **Fragility Factor:** Moderately rugged **Mounting Surface To Terminal End Distance:** 1.780 inches **Pole Quantity: Mounting Facility Type And Quantity:** 1 threaded bushing w/panel seal Storage Type: General purpose warehouse **Special Handling Feature:** Magnetic Thready Qty Per Inch (tpi): **Maximum Continuous Load Current Rating Per Pole:** 10.0 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 240.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 300.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Magnetic all locations **Trip Release Characteristic:** 

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 

125.0 all locations

## **NSN 5925-01-361-5511** Circuit Breaker - Page 2 of 2



Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
Between pole one and two
Internal Trip Release Configuration:
Series trip all locations
Thread Size:
0.375 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
0.200 at 200 pct all locations and 7.000 at 200 pct all locations
Inclosure Protection Type For Which Designed:
Shockproof and vibrationproof and hermetically sealed
Frequency In Hertz:
50.0 all locations or 60.0 all locations
Unpackaged Unit Weight:
3.600 ounces
Thread Series Designator:
Unef
Terminal Type And Quantity:
4 wire hook
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0