NSN 5925-01-361-7671

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-361-7671

| Body Style: |
|---|
| Single pole type |
| Body Length: |
| 2.500 inches |
| Body Width: |
| 0.750 inches |
| Case Material: |
| Plastic |
| Center To Center Distance Between Terminals Parallel To Length: |
| 1.938 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length |
| 2.062 inches |
| Boss Height: |
| 0.140 inches |
| Mounting Surface To Terminal End Distance: |
| 2.720 inches |
| Pole Quantity: |
| 1 |
| Mounting Facility Type And Quantity: |
| 2 clip |
| Maximum Continuous Load Current Rating Per Pole: |
| 15.0 amperes ac single location |
| Operating Voltage Type And Rating Per Pole In Volts: |
| 250.0 ac single location |
| Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: |
| 5000.0 ac single location |
| Circuit Protection Type: |
| Overcurrent single location |
| Trip Release Method: |
| Magnetic-hydraulic single location |
| Trip Release Characteristic: |
| Time delay single location |
| Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: |
| 125.0 single location |
| Reset Method: |
| Manual |
| Main Contact Tripping Mechanism Type: |
| Trip free |
| Internal Trip Release Configuration: |
| Series trip single location |
| |

Trip Delay Time In Seconds Per Rated Continuous Current:

2.000 at 200 pct single location and 20.000 at 200 pct single location

NSN 5925-01-361-7671

Circuit Breaker - Page 2 of 2



| Frequency In Hertz: | Freq | uency | In | Her | tz: |
|---------------------|------|-------|----|-----|-----|
|---------------------|------|-------|----|-----|-----|

60.0 single location

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0