## NSN 5925-01-361-7671

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-361-7671

| Body Style:   |
|---|
| Single pole type  |
| Body Length:  |
| 2.500 inches  |
| Body Width:   |
| 0.750 inches  |
| Case Material:  |
| Plastic   |
| Center To Center Distance Between Terminals Parallel To Length:             |
| 1.938 inches  |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length |
| 2.062 inches  |
| Boss Height:  |
| 0.140 inches  |
| Mounting Surface To Terminal End Distance:                                  |
| 2.720 inches  |
| Pole Quantity:  |
| 1   |
| Mounting Facility Type And Quantity:  |
| 2 clip  |
| Maximum Continuous Load Current Rating Per Pole:                            |
| 15.0 amperes ac single location   |
| Operating Voltage Type And Rating Per Pole In Volts:                        |
| 250.0 ac single location  |
| Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:     |
| 5000.0 ac single location   |
| Circuit Protection Type:  |
| Overcurrent single location   |
| Trip Release Method:  |
| Magnetic-hydraulic single location  |
| Trip Release Characteristic:  |
| Time delay single location  |
| Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:      |
| 125.0 single location   |
| Reset Method:   |
| Manual  |
| Main Contact Tripping Mechanism Type:                                       |
| Trip free   |
| Internal Trip Release Configuration:  |
| Series trip single location   |
|   |

Trip Delay Time In Seconds Per Rated Continuous Current:

2.000 at 200 pct single location and 20.000 at 200 pct single location

## NSN 5925-01-361-7671

Circuit Breaker - Page 2 of 2



| Frequency In Hertz: | Freq | uency | In | Her | tz: |
|---------------------|------|-------|----|-----|-----|
|---------------------|------|-------|----|-----|-----|

60.0 single location

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A030a0