

View Online at <https://aerobasegroup.com/nsn/5925-01-361-7683>

**Body Style:**

Multipole-single actuator type

**Body Length:**

2.000 inches

**Body Width:**

1.540 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

1.250 inches

**Center To Center Distance Between Terminals Parallel To Width:**

0.625 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

1.610 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.625 inches

**Boss Height:**

0.125 inches

**Mounting Surface To Terminal End Distance:**

1.770 inches

**Pole Quantity:**

2

**Mounting Facility Type And Quantity:**

4 clip

**Maximum Continuous Load Current Rating Per Pole:**

20.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

250.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

2000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

115.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

Between pole one and two

**Internal Trip Release Configuration:**

Series trip all locations

**Trip Delay Time In Seconds Per Rated Continuous Current:**

0.500 at 200 pct all locations and 9.000 at 200 pct all locations

**Frequency In Hertz:**

50.0 all locations or 60.0 all locations

**Terminal Type And Quantity:**

4 quick disconnect, male

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0