## NSN 5925-01-361-8447

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-361-8447 **Bushing Length:** 0.625 inches **Body Length:** 2.000 inches **Body Width:** 2.265 inches **Case Material:** Plastic **Center To Center Distance Between Terminals Parallel To Length:** 1.530 inches **Center To Center Distance Between Terminals Parallel To Width:** 0.750 inches **Mounting Surface To Terminal End Distance:** 2.232 inches **Pole Quantity: Mounting Facility Type And Quantity:** 1 threaded bushing w/panel seal Thready Qty Per Inch (tpi): 32 **Maximum Continuous Load Current Rating Per Pole:** 25.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 240.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 1000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Magnetic all locations **Trip Release Characteristic:** Time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 all locations **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 1 toggle

Trip-reset

**Actuator Function:** 

## NSN 5925-01-361-8447

Circuit Breaker - Page 2 of 2



Actuator Position Designation:
At pole two
nternal Trip Release Configuration:
Series trip all locations
Thread Size:
0.500 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
3.000 at 200 pct all locations and 20.000 at 200 pct all locations
Frequency In Hertz:
60.0 all locations
Test Data Document:
81349-mil-c-55629 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Jn
Ferminal Type And Quantity:
Stab, solder lug
Specification Data:
31349-mil-c-55629/22 government specification
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No
Filg:
A030a0