

View Online at <https://aerobasegroup.com/nsn/5925-01-363-3127>

Body Style:

Multipole-single actuator type

Body Length:

345.9 millimeters

Body Width:

139.2 millimeters

Body Height:

103.1 millimeters

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

180.8 millimeters

Center To Center Distance Between Terminals Parallel To Width:

33.0 millimeters

Unthreaded Mounting Hole Diameter:

9.9 millimeters

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

218.9 millimeters

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

91.9 millimeters

Fragility Factor:

Moderately rugged

Boss Height:

6.4 millimeters

Pole Quantity:

3

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

6 unthreaded hole

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Maximum Continuous Load Current Rating Per Pole:

50.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

600.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

50000.0 ac all locations

Circuit Protection Type:

Undervoltage all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Instantaneous all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

138.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Internal Trip Release Configuration:

Shunt trip all locations

Inclosure Protection Type For Which Designed:

Humidity proof and fungus proof

Frequency In Hertz:

50.0 all locations or 60.0 all locations

Precious Material And Location:

Contact surfaces silver

Precious Material:

Silver

Terminal Type And Quantity:

6 bus bar

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0