

View Online at <https://aerobasegroup.com/nsn/5925-01-363-3239>

Overall Length:

50.8 millimeters

Body Width:

15.8 millimeters

Case Material:

Metal

Center To Center Distance Between Terminals Parallel To Length:

17.2 millimeters

Unthreaded Mounting Hole Diameter:

5.6 millimeters

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

39.6 millimeters

Mounting Surface To Terminal End Distance:

34.9 millimeters

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 unthreaded hole

Maximum Continuous Load Current Rating Per Pole:

50.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

12.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic single location

Trip Release Characteristic:

Instantaneous single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Reset Method:

Automatic

Internal Trip Release Configuration:

Series trip single location

Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0