

View Online at <https://aerobasegroup.com/nsn/5925-01-363-6282>

Body Style:

Rectangular dimensional envelope

Overall Length:

1.930 inches

Overall Height:

0.710 inches

Overall Width:

1.180 inches

Case Material:

Plastic

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 clip

Maximum Continuous Load Current Rating Per Pole:

25.0 amperes ac single location and 25.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac single location and 28.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

2000.0 ac single location and 2000.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

140.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Series trip single location

Trip Delay Time In Seconds Per Rated Continuous Current:

20.000 at 200 pct single location and 70.000 at 200 pct single location

Frequency In Hertz:

60.0 single location

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0