

View Online at <https://aerobasegroup.com/nsn/5925-01-364-2565>

**Body Style:**

Rectangular dimensional envelope

**Overall Length:**

1.770 inches

**Overall Height:**

0.771 inches

**Overall Width:**

2.000 inches

**Case Material:**

Plastic

**Pole Quantity:**

1

**Mounting Facility Type And Quantity:**

2 clip

**Maximum Continuous Load Current Rating Per Pole:**

15.0 amperes ac single location

**Operating Voltage Type And Rating Per Pole In Volts:**

250.0 ac single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

1000.0 ac single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Magnetic single location

**Trip Release Characteristic:**

Time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 single location

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole one

**Internal Trip Release Configuration:**

Series trip single location

**Trip Delay Time In Seconds Per Rated Continuous Current:**

2.000 at 200 pct single location and 20.000 at 200 pct single location

**Frequency In Hertz:**

50.0 single location or 60.0 single location

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0