

View Online at <https://aerobasegroup.com/nsn/5925-01-365-9941>

**Body Style:**

Multipole-multiple actuator type

**Body Length:**

2.500 inches

**Body Width:**

3.000 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

1.938 inches

**Center To Center Distance Between Terminals Parallel To Width:**

0.750 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

2.062 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.750 inches

**Boss Height:**

0.140 inches

**Mounting Surface To Terminal End Distance:**

2.611 inches

**Pole Quantity:**

4

**Mounting Facility Type And Quantity:**

8 threaded hole

**Maximum Continuous Load Current Rating Per Pole:**

10.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

250.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

1000.0 ac all locations

**Circuit Protection Type:**

Overcurrent first locationovercurrent second locationovercurrent third locationundervoltage fourth location

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Time delay first locationtime delay second locationtime delay third locationinstantaneous fourth location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

4 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At each pole

**External Actuator Linkage Arrangement:**

One, two, three, and four linked

**Internal Trip Release Configuration:**

Series trip first locationseries trip second locationseries trip third locationrelay trip fourth location

**Thread Size:**

0.138 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

2.000 at 200 pct first location and 20.000 at 200 pct first location2.000 at 200 pct second location and 20.000 at 200 pct second location2.000 at 200 pct third location and 20.000 at 200 pct third location

**Frequency In Hertz:**

400.0 first location400.0 second location400.0 third location60.0 fourth location

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

10 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0